


**TECHNICAL SPECIFICATION OF THE REQUESTED EQUIPMENT
FOR CCSMO**

| ITEM | QUANTITY | SPECIFICATION |
|--|-------------------------------|--|
| <p>DSLR Mirrorless Camera <i>(Canon EOS M50 Mark II)</i></p> | <p align="center">3 units</p> | <p>Key Features 24.1MP APS-C CMOS Sensor DIGIC 8 Image Processor UHD 4K and HD 720p120 Video Recording Dual Pixel CMOS AF with Eye Detect AF 2.36m-Dot OLED Electronic Viewfinder 3.0" 1.04m-Dot Vari-Angle Touchscreen Wi-Fi and Bluetooth; Webcam Capability Extended ISO 51200, 10 fps Shooting Combination 5-Axis Image Stabilization EF-M 15-45mm f/3.5-6.3 IS STM Lens Canon LP-E12 Lithium Battery Pack (7.2V, 875mAh) Canon Battery Charger LC-E12 for Battery Pack LP-E12</p> |
| <p>Wide Angle Lens (for Canon EOS M50 Mirrorless Camera) – <i>Canon EF-M 11-22mm F/4-5.6 IS STM</i></p> | <p align="center">1 unit</p> | <p>Product Highlights EF-M Mount Lens/APS-C Format 18-35mm (35mm Equivalent) Aperture Range: f/4.5-32 Two Aspherical Elements One UD Element Dynamic Image Stabilization Spectra Coatings Built-In Stepping Motor</p> |
| <p>Telephoto Lens (for Canon EOS M50 Mirrorless Camera) – <i>Canon EF-M 18-150mm f/3.5-6.3 IS STM</i></p> | <p align="center">1 unit</p> | <p>Key Features EF-M-Mount Lens/APS-C Format 28.8-240mm (35mm Equivalent) Maximum Aperture: f/3.5-6.3 STM Autofocus System Optical Image Stabilizer Combination IS and Stabilized Panning Covering wide-angle to telephoto focal lengths, the graphite EF-M 18-150mm f/3.5-6.3 IS STM from Canon is an 8.3x zoom designed for EF-M-mount mirrorless cameras, where it provides a 28.8-240mm equivalent focal length.</p> |
| <p>Extra Battery (for Canon EOS M50 Mirrorless Camera) – <i>LP-E12 Lithium-Ion Battery</i></p> | <p align="center">2 pcs.</p> | <p>Key Features 7.2V Output 875mAh Capacity Powers EOS M50 and M100 Cameras For Rebel SL1 & PowerShot SX70 HS</p> |

| | | |
|---|---------------|--|
| <p>Extra Battery (for Sony Video Camera) – NP-FV100A V-Series Rechargeable</p> | <p>2 pcs.</p> | <p>Key Features InfoLITHIUM V Series Handycam Battery Extended Capacity Model Remaining Life Display on Select Cameras Compatible with AC-VQH10 Charger The Sony NP-FV100A V-Series Rechargeable Battery Pack is compatible with all Handycam camcorders and features a 3410mAh capacity. Part of Sony's InfoLITHIUM V Series, this battery is designed to communicate remaining life in minutes on compatible cameras LCDs.</p> |
| <p>External Flash (for Canon EOS M50 Mirrorless Camera) – Canon Speedlite 470EX-AI</p> | <p>1 unit</p> | <p>Key Features Auto Intelligent Bounce Head Compatible with Canon E-TTL/E-TTL II Guide Number: 154' at ISO 100 and 105mm Zoom Range: 24-105mm (14mm with Panel) Tilts Upward 120°, +/- 180° Rotation AI.B Full-Auto and AI.B Semi-Auto Modes Optical Receiver Mode LCD Panel AF Assist Beam Runs on 4x AA Batteries</p> |
| <p>Heavy Duty Tripod – Benro KH25P Video Head & Tripod Kit</p> | <p>1 unit</p> | <p>Key Features 11 lb Capacity Video Head Sliding Balance Plate 29.5 to 61.6" Height Range Continuous Pan Drag/Fixed Tilt Drag 2 x Retracting Locating Pins on Plate 60mm Leveling Ball 2-Stage Tripod with Mid-Level Spreader Independent Twist-Lock Leg Adjustment Dual Spiked Feet & Rubber Feet Padded Carrying Case</p> |

Prepared by:


RAFAEL B. BARIANTOS
Public Relations Officer

Noted by:

 11/14/23
ELLEN FLEUR V. BANG-AY
Public Relations Chief